| LID CW3660B 176 X 2 LBS | | |
|---|---|---|
| ENCLOSURE BV366048 439 LBS ASSEMBLY AV366048W 753 LBS PALLET QTY 1 841 LBS LOAD RATINGS TIER-15, TIER-22 66.8 | 39.2 | GLASMASTERS, INC. 8873 WESTERN WAY, JAX., FL 32256 (904) 400-7100 - (904) 358-1702 FAX WWW.GLASMASTERS.COM |
| 59.8 | POLYMER CONCRETE COVER POLYMER | DATE APPROVED SJA SJA |
| 48.0 | CONCRETE RING 1/2-13 U-BOLT FOR LIFITNG (4PLCS) FIBERGLASS SHELL POLYMER CONCRETE FOOT | RRUGATED ASSY BMC BMC REV HLE |

THIS DRAWING IS CONFIDENTIAL AND PROPRIETARY AND MAY NOT BE DISTRIBUTED OR REPRODUCED WITHOUT THE EXPRESSED WRITTEN CONSENT OF GLASMASTERS, INC. ALL COPYRIGHT AND PATENT RIGHTS RESERVED. VIOLATORS WILL BE PROSECUTED.

SHEET | ITTLE | SAGO | SCALE | DWG NO | OF 1 | 1:24 | AV3660